







### **Product Description:**

## Rapid SL 5-in-1 set for WC

# Standard Specification: flushing cistern GD 2 1.13 m installation height

for on-the-wall installations or studded walls for dry-cladding, completely pre-assembled powder coated steel frame, self-supporting with fixed connections

quick adjustment, lockable

fixing material

TÜV approved

2 WC fixing bolts

fixing device for ceramic

WC ceramics with small bearing area (less than 205 mm) require additional accessory 38 779 000

distance of fixing bolts 180/230 mm

outlet bend Ø 90 mm

depth adjustable

depth adjustable

reducer Ø 90/110 mm

inlet and outlet connecting set

## flushing cistern GD 2, 6 - 9 I

adjustment ex factory 6 I and 3 I

pneumatic discharge valve offering 3 modes of

operation: dual flush or start/stop or single flush

water supply from left/right or back

low noise (group I acc. to German Noise Specification)

insulated against condensation

½" water supply connection including integrated angle valve and push fit flexible hose union

no tools required for the installation of the inspection shaft

including protection during construction phase

for vertical or horizontal use

accessories for on-the-wall installation

#### toilet brush set, wall mounted

with GROHE Fresh retrofit set

for chlorine-free tabs only

including flush plate Skate Cosmopolitan

vertical and horizontal installation

156 x 197 mm

chrome

made of ABS

GROHE StarLight chrome finish

WC set for noise protection

Pure Freude an Wasser



Color:

□ 39000000 chrome